

IR SUPPLIES AND SERVICES 8108 McIntyre Road Edmonton, AB T6E 5C4 PH: (780) 452-4761

FAX: (780) 453-5239



Portable LED Film Viewer

FV-2010 Plus

- Electronic Light Mask
- Larger Size 400 x 100 mm (15.8" x 4")
- Low Noise
- CE Approved

MAX.L=130,000Cd/m²

g = 0.95

 $\sigma' = 0.95$

Characteristics:

Luminance: 130,000 Cd/M² (408,200 Lux)

High Accuracy: ± 0.02D

• Uniformity: 0.95, Diffusion factors: 0.95

- Weighs less than 4.0 Kg (8.8lbs)
- 12 hours continuous maximum luminance
- Adjustable dimmer from 5%- 100%
- Free 2 years' service guarantee
- CE Approved

Specifications:

Diffusion Factor: σ'= 0.95

• Dimension: 600 x 80 x 160 mm

23.6" x 3.1" x 6.3" inch

Window Size: 400 x 100mm (15.8" x 4")

Surface temperature rise ≤ 18°^c

Power: 85-264 VAC 47~63 Hz.

(Full Range)

Electronic Light Mask

New for the FV-2010 series of LED Viewers!!!

With the push of a button you can instantly change the size of the viewing window! No more light masks! The new design of the FV-2010 series of High Intensity LED Film Illuminators you can change the size of the viewing window with the click of a button.

The size of light can be switched to the sizes below:

15.8×4 2.7×4 5.4×4 8.1×4 10.8×4