



INDUSTRIAL RADIOGRAPHY SUPPLIES AND SERVICES

8108 McIntyre Road
 Edmonton, AB T6E 5C4
 PH: (780) 452-4761
 IRSS.CA
 The Canadian LCNDT Distributor



FV-2009T

LED Industrial Film Viewer

MAX. L ≥ 73,000 Cd/m² g ≥ 0.95 σ ≥ 0.95

Characteristics:

- Portable LED film viewer combined with a Densitometer
- High Luminance: ≥ 110,000 Cd/m²
- Density: 4.1 H/D
- Viewing Screen: 8' X 2.5' (200 X 60 mm)
- High Accuracy: ± 0.02D
- Separated design, for easy maintenance
- Rugged design, aluminum alloy
- Two year limited manufactures warranty

The FV-2009 LED viewer has been developed in accordance with ISO5580 Standards "Industrial Radiographic Illuminators". The LED bulb life expectancy is up to 50,000 hours.

Featuring an ergonomic, portable and rugged design the FV-2009T is suitable for auditors and quality assurance professionals. Lightweight and easily portable the unit excels as a stationary unit or as a mobile QC tool. The FV-2009T viewer has a fully adjustable intensity and capable of reading a density of up to 4.1 H/D.

SPECIFICATION:

Max Luminance: ≥ 110,000Cd/m ²	Uniformity: g≥0.95
Diffusion Factor: σ≥0.95	Viewer Window: 8'X2.5' (200x60mm)
Surface Temp. Rise: ≤15°C	Power: 85-264VAC 47~63Hz (Full Range)
Dimensions: 18'X5.5'X2.5' (LxWxH)	Weight: 5.5lbs (2.5 kg)

INCLUDED:

Foot Pedal
Carrying Case
Instructions (English)
Guarantee/Report
Built in Densitometer
Light Mask (150x45mm) (150x60mm)