



**IR SUPPLIES AND SERVICES**  
 8108 McIntyre Road  
 Edmonton, AB T6E 5C4  
 PH: (780) 452-4761  
 FAX: (780) 453-5239



## Portable LED Film Viewer Combined With Densitometer

# FV-2010T Plus

- High Accuracy Densitometer:  $\pm 0.02D$
- Electronic Light Mask
- Larger Size 400 x 100 mm (15.8" x 4")
- Low Noise
- CE Approved

**MAX.L=130,000Cd/m<sup>2</sup>**

**g=0.95**

**$\sigma'$ =0.95**

### Characteristics:

- Luminance: 130,000 Cd/M<sup>2</sup> (408,200 Lux)
- High Accuracy:  $\pm 0.02D$
- Uniformity: 0.95, Diffusion factors: 0.95
- Weighs less than 4.0 Kg (8.8lbs)
- 12 hours continuous maximum luminance
- Adjustable dimmer from 5%- 100%
- Free 2 years' service guarantee
- CE Approved

### Specifications:

- Diffusion Factor:  $\sigma' = 0.95$
- Dimension: 600 x 80 x 160 mm  
23.6" x 3.1" x 6.3"
- Window Size: 400 x 100mm (15.8" x 4")
- Surface temperature rise  $\leq 18^{\circ}C$
- Power: 85-264 VAC 47~63 Hz.  
(Full Range)

### Electronic Light Mask

#### **New for the FV-2010 series of LED Viewers!!!**

With the push of a button you can instantly change the size of the viewing window! No more light masks! With the new design of the FV-2010 series of High Intensity LED Film Illuminators you can change the size of the viewing window with the click of a button.

**The size of light can be switched to the sizes below:**

