

SAFETY DATA SHEET



Version 16.1 replaces Version 15.2
Revision date: 29/07/2016
According to (EU) No. 2015/830

SECTION 1

IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

- 1.1 Product identifier:** SPOTCHECK® SKL-WP2 - aerosol
- 1.2 Relevant identified uses of the mixture and uses advised against:**
Relevant identified uses: Red penetrant used in Non Destructive Testing (NDT) inspection.
Uses advised against: This product is not recommended for any use other than the identified uses above.
- 1.3 Details of the supplier of the safety data sheet**
Manufacturer: Magnaflux® (A Division of ITW Ltd)
Address: Faraday Road, South Dorcan Industrial Estate, Swindon, UK
Postcode: SN3 5HE
Telephone/fax number: Telephone: +44 (0)1793 524566
Fax: +44 (0)1793 490459
Web: www.eu.magnaflux.com
Email address of competent person responsible for SDS: datasheets@magnaflux.co.uk
National contact: None appointed.
- 1.4 Emergency telephone number:** T: +44 (0)1793 524566 (office hours)
Opening hours: Office hours (GMT) Monday - Thursday 8am - 5pm, Friday 8am - 4pm
Other comments: Emergency telephone service is provided in English only.

SECTION 2

HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
Classification according to Regulation (EC) No 1272/2008 (CLP): **Physical and Chemical Hazard:** Aerosol 1 H222, H229
Health Hazard: Eye Dam. 1 H318
Environmental Hazard: Aquatic Chronic 3 H412
EUH066
Additional information
For full text of hazard statements and EU hazard statements see SECTION 16.

SAFETY DATA SHEET

2.2

Label Elements:

Labelling according to regulation (EC) No 1272/2008 [CLP]

Hazard Pictograms:



Signal Word:

Hazard Statement(s):

Danger

H222: Extremely flammable aerosol

H229: Pressurised container. May burst if heated.

H318: Causes serious eye damage.

H412: Harmful to aquatic life with long lasting effects

Precautionary Statement(s):

P210: Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do – continue rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501: Dispose of contents/container to hazardous waste or special collection point.

Supplementary Precautionary Statement(s):

P243: Take precautionary measures against static discharge.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.
EUH066: Repeated exposure may cause skin dryness or cracking.

Supplementary Hazard Information (EU)

Hazard Determining Component(s)

Alcohols, C12-C15, branched and linear, ethoxylated, propoxylated
ALCOHOLS, C11 – C15 SECONDARY ETHOXYLATED

Oleic acid monoisopropanolamide

2.3

Other hazards:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C.

Vapours can form explosive mixtures in air.

Product may stain skin.

SAFETY DATA SHEET

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

| Ingredient Name | CAS No | EC No | REACH Registration Number | % Weight | Classification according to Regulation (EC) No 1272/2008 [CLP] | Additional information |
|---|-------------|-----------|---------------------------|----------|--|---|
| Hydrocarbons C12-C15 n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS | - | 920-107-4 | 01-2119453414-43-xxxx | < 40 | Asp. Tox. 1 H304 (note 1) | EUH066 |
| Hydrocarbons, C3-4-rich petroleum distillate petroleum gas (1,3 butadiene < 0.1%) | 68512-91-4 | 270-990-9 | (note 2) | < 40 | Press. Gas H280 Flam. Gas 1 H220 | (note 3) |
| Alcohols, C12-C15, branched and linear, ethoxylated, propoxylated | 120313-48-6 | - | - | < 10 | Eye Dam. 1 H318 Aquatic Chronic 2 H411 | None |
| ALCOHOLS, C11 – C15 SECONDARY ETHOXYLATED | 68131-40-8 | 614-295-4 | - | < 7 | Eye Dam. 1 H318 Skin Irrit. 2 H315 | None |
| 2-Naphthalenamine, N-(2-ethylhexyl)-1-[[4-phenylazo]phenyl]azo]-, ar' and ar'' – Me derivs. | 92257-28-8 | 296-117-1 | - | < 3 | Not classified | See Section 11 for information on azo dyes. |
| Oleic acid monoisopropanolamide | 111-05-7 | - | - | < 2 | Eye Dam. 1 H318 Skin Irrit. 2 H315 | None |
| Terpineol | 8000-41-7 | 232-268-1 | - | < 2 | Eye Irrit. 2 H319 Skin Irrit. 2 H315 | None |
| Solvent naphtha (petroleum), heavy arom. | 64742-94-5 | 265-198-5 | - | < 2 | Asp. Tox. 1 H304 Aquatic Chronic 2 H411 | None |
| 1. Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. 2. Exempted from the obligation to register in accordance with art.2(7)(a) of REACH Regulation No 1907/2006 3. Not classified as carcinogen, less than 0.1% w/w 1,3 butadiene (EINECS no 203-450-8) | | | | | | |

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished products.

**See Section 16 for hazard statement(s) text in full.*

SECTION 4

FIRST AID MEASURES

4.1 Description of first aid measures:

General notes:

If symptoms persist, seek medical attention. Show this safety data sheet to the doctor in attendance.

Following inhalation:

Remove to fresh air. Keep at rest. If not breathing give artificial respiration. Seek medical attention if symptoms occur.

Following skin contact:

Flush with water, use soap if available. Contaminated clothing should be washed before re-use. Seek medical attention if symptoms occur.

Following eye contact:

Flush eyes with large amounts of water for at least 15 minutes. Check for and remove any contact lenses if easy to do. Continue rinsing. Seek medical attention immediately.

Following ingestion:

Unlikely route of exposure. Rinse mouth with water. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach contents don't enter the lungs. Never give anything by mouth to an unconscious person. Seek medical attention immediately.

SAFETY DATA SHEET

Self-protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate personal protective equipment.

- 4.2 Most important symptoms, both acute and delayed:**
Risk of serious damage to eyes, may cause lung damage if swallowed, no delayed effects known.
- 4.3 Indication of any immediate medical attention and special treatment needed:**
Eye wash bottle must be readily available when product is in use.

SECTION 5 FIREFIGHTING MEASURES

- 5.1 Extinguishing media:**
Suitable extinguishing media: Carbon dioxide, foam, dry chemical, water fog or spray.
Unsuitable extinguishing media: Do not use water jet.
- 5.2 Special hazards arising from the substance or mixture:** Evacuate immediate area. Shut off 'fuel' to fire. If possible keep unaffected containers cool with water spray.
Aerosols may explode in a fire.
Aerosol contents are extremely flammable.
Hazardous combustion products: Smoke, soot and oxides of carbon. Burning vapour may give off toxic fumes.
- 5.3 Advice for fire-fighter:**
Warn firefighters that aerosols are involved.
Self contained breathing apparatus and full protective clothing must be worn.
Water spray should be used to cool containers.

SECTION 6 ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures:**
Suitable protective equipment (see Section 8) should be worn to prevent any contamination of skin, eyes and personal clothing.
For non-emergency personnel: Remove ignition sources. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Vapours are likely to accumulate in low areas.
For emergency responders: Remove ignition sources. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Vapours are likely to accumulate in low areas. Keep unnecessary people at a safe distance.
- 6.2 Environmental precautions:**
Prevent liquid from entering drains, sewers and watercourses. Notify the Environment Agency or water authorities if a major spillage occurs. Prevent product contaminating soil.
- 6.3 Methods and material for containment and cleaning up:**
Eliminate sources of ignition. Take measures to prevent the build-up of electrostatic charge. Ventilate surrounding area.

SAFETY DATA SHEET

For containment:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Place in a UN approved container for disposal.

Large spills should be pumped (using an earthed explosion proof pump) into UN approved containers pending disposal. Dispose of waste according to local/national regulations.

For cleaning up:

Do not flush away residues with water.

Other information:

No other information.

6.4

Reference to other sections:

For Personal Protective Equipment see Section 8. For disposal information see Section 13.

SECTION 7

HANDLING & STORAGE

7.1

Precautions for safer handling:

Protective Measures:

Wear suitable protective clothing such as chemical resistant gloves, apron and goggles/face mask to protect from splashes. Ensure adequate exhaust ventilation when in use.

Avoid contact with skin and eyes.

Do not breathe product spray or mist.

Aerosol contents are highly flammable and volatile. Keep away from sources of ignition – no smoking.

Take measures to prevent the build-up of electrostatic charge.

Equipment should be earthed. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

Wash thoroughly after handling.

Measures to prevent fire:

Advice on general occupational hygiene:

7.2

Conditions for safe storage, including any incompatibilities:

Technical measures and storage conditions:

Packaging materials:

Store in a cool dry area away from heat and sources of ignition.

Store in original container. Keep containers tightly closed when not in use.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C.

Recommended storage temperature 10 °C to 30 °C.

Rotate stock and check regularly for damaged items.

Requirements for storage rooms and vessels:

Further information on storage conditions:

7.3

Specific end use(s):

Recommendations:

Use only for Non Destructive Testing (NDT) applications.

Industrial sector specific solutions:

See product data sheet for further information.

SAFETY DATA SHEET

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

Occupational exposure limit values:

Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

| Ingredient name | Country | Limit value - 8 hours | | Limit value - short term | |
|--|---------------------------|-----------------------|--------------------|--------------------------|--------------------|
| | | ppm | mg /m ³ | ppm | mg /m ³ |
| Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics | Supplier's recommendation | 150 | 1200 | | |

Data obtained from supplier's SDS

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) – Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

| End User | Exposure Route | Exposure Time | Effects | DNEL |
|----------|----------------|---------------|----------|--|
| Worker | Inhalation | Long term | Systemic | No threshold effect and/or no dose-response information available. |
| Worker | Inhalation | Short term | Local | No threshold effect and/or no dose-response information available. |
| Worker | Dermal | Long term | Systemic | No threshold effect and/or no dose-response information available. |

Derived No Effect Level (DNEL) – Terpineol

| End User | Exposure Route | Exposure Time | Effects | DNEL |
|----------|----------------|---------------|----------|-----------------------|
| Worker | Inhalation | Long term | Systemic | 5.8 mg/m ³ |
| Worker | Inhalation | Short term | Systemic | 5.8 mg/m ³ |
| Worker | Dermal | Long term | Systemic | 1.17 mg/kg bw/day |
| Worker | Dermal | Short term | Systemic | 5 mg/kg bw/day |

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

SAFETY DATA SHEET

Predicted No Effect Concentration (PNEC)

| | | |
|------------------------------|--|-------------------------|
| | Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics | Terpineol |
| Water - Fresh Water | No data available, testing technically not feasible. | 62 µg/L |
| Water - Marine Water | No data available, testing technically not feasible. | 6.2 µg/L |
| Water - Intermittent release | No data available, testing technically not feasible. | No data available. |
| Sediment - Fresh water | No data available, testing technically not feasible. | 0.442 mg/kg sediment dw |
| Sediment - Marine water | No data available, testing technically not feasible. | 0.044 mg/kg sediment dw |
| Soil | No data available, testing technically not feasible. | 0.052 mg/kg soil dw |
| Sewage Treatment plant | No data available, testing technically not feasible. | 2.57 mg/L |

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable. Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

Appropriate engineering controls:

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded.
Provide eye wash station.

Personal protection equipment:

Eye and face protection:

Safety glasses with side-shields conforming to EN166.

Skin protection - hand:

Protective gloves conforming to EN374-3. Use chemical resistant gloves recommended by glove manufacturer as being suitable for **kerosenes** if hand exposure is unavoidable. Protective gloves made of nitrile, neoprene or PVC are suitable, although other types may be more suitable in other circumstances. For prolonged exposure, recommended gloves with protective index 6, > 480 minutes permeation time according to EN374.

Skin protection – other:

As the product is a preparation, consult the glove manufacturer for exact breakthrough time. Glove manufacturer's directions for use should be observed. Wear impervious, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the specific workplace.

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Filter type A2. (EN 136, 140, 405, 149, 143) For higher level protection use type ABEK-P3 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under CEN standards.

SAFETY DATA SHEET

Thermal hazards:

Not applicable.

Environmental exposure controls:

Avoid any release to the environment.

SECTION 9

PHYSICAL & CHEMICAL PROPERTIES

| | | |
|------------|---|-------------------------------------|
| 9.1 | Information on basic physical and chemical properties: | |
| | Appearance: | Aerosol containing dark red liquid. |
| | Odour: | Mild pine. |
| | Odour threshold: | No data available. |
| | pH: | Neutral |
| | Melting point/freezing point: | No data available. |
| | Initial boiling point and boiling range: | 230 °C. |
| | Flash point (PMCC): | -40 °C (aerosol propellant) |
| | Evaporation rate (BuAC = 100): | < 0.1. |
| | Flammability (solid, gas) (Limits in air): | No data available. |
| | Upper/lower flammability or explosive limits: | 1 – 6% (Vol%). |
| | Vapour pressure: | < 0.5 mm Hg @ 38 °C. |
| | Vapour density (Air = 1): | > 1 |
| | Relative density: | 0.88 g/cm ³ |
| | Solubility: | Emulsifies. |
| | Partition coefficient: n-octanol/water: | No data available. |
| | Auto-ignition temperature: | > 200 °C. |
| | Decomposition temperature: | No data available. |
| | Viscosity (ASTM D445): | 8.0 mm ² /s @ 38 °C. |
| | Explosive properties: | No data available. |
| | Oxidising properties: | No data available. |

Note: properties relate to the bulk product only unless otherwise stated.

| | |
|------------|---------------------------|
| 9.2 | Other information: |
| | No other information. |

SECTION 10

STABILITY & REACTIVITY

| | | |
|-------------|--|---|
| 10.1 | Reactivity: | No data available. |
| 10.2 | Chemical stability | Stable under normal conditions of use and applications. |
| 10.3 | Possibility of hazardous reactions: | No data available. |
| 10.4 | Conditions to avoid: | Keep away from sources of ignition, hot surfaces, direct sunlight and static discharge. |
| 10.5 | Incompatible materials: | Strong oxidizing agents. Acids and alkalis. |
| 10.6 | Hazardous decomposition materials: | None under normal conditions of storage and use. Smoke, soot and oxides of carbon and nitrogen on combustion. |

SAFETY DATA SHEET

SECTION 11

TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: based on data for component materials.

| | |
|---------------------------------------|--|
| Acute toxicity - oral: | Based on the available data the classification criteria are not met. |
| Acute toxicity – dermal: | Based on the available data the classification criteria are not met. |
| Acute toxicity – inhalation: | Based on the available data the classification criteria are not met. |
| Skin corrosion/irritation: | Skin Irrit. 2, H315: Causes skin irritation. EUH066: Repeated exposure may cause skin cracking or dryness. |
| Serious eye damage/irritation: | Eye Dam. 1, H318: Causes serious eye damage. |
| Respiratory sensitisation: | Based on tests of individual components, this preparation is not sensitising. |
| Skin sensitisation: | Based on tests of individual components, this preparation is not sensitising. |
| Germ cell mutagenicity: | Based on individual components, this preparation is not expected to show mutagenic effects. |
| Carcinogenicity: | Based on individual components, this preparation is not expected to show carcinogenic effects. |
| Reproductive toxicity: | Based on individual components, this preparation is not expected to show reproductive toxicity. |
| STOT single exposure: | Data lacking. |
| STOT repeated exposure: | Data lacking. |
| Aspiration hazard: | Mixtures from Aerosol Dispensors - need not be classified as Asp. Tox. 1 - H304 as the aerosol spray is fine and a pool of product may not be formed in the mouth. |

Information on likely Routes of Exposure and Potential Health Effects:

| | |
|----------------------|---|
| Inhalation: | May be harmful if inhaled. Causes respiratory tract irritation. |
| Ingestion: | Not a likely route of entry. However, may be harmful if swallowed. Ingestion may cause irritation of the mouth, throat and digestive tract. Small amounts of product aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary edema. |
| Eye contact: | Risk of serious damage to eyes. |
| Skin contact: | May be harmful if absorbed through skin. Causes skin irritation. Repeated exposure may cause skin cracking or dryness. |

Toxicity Test Results: based on data for component materials, where available.

Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

| | | |
|-----------------------------|---------------|----------------------------------|
| Acute Toxicity – oral | LD50 (rat) | > 5000 mg/kg (OECD 401) |
| Acute Toxicity – dermal | LD50 (rabbit) | > 5000 mg/kg (OECD 402) |
| Acute Toxicity – inhalation | LC50 (rat) | 4951 mg/l (vapours) 4h (OECD403) |

SAFETY DATA SHEET

Alcohols, C12-C15, branched and linear, ethoxylated, propoxylated

| | | |
|-----------------------------|---------------|---------------------|
| Acute Toxicity – oral | LD50 (rat) | 2,000 – 5,000 mg/kg |
| Acute Toxicity – dermal | LD50 (rabbit) | Not determined |
| Acute Toxicity – inhalation | LC50 (rat) | Not determined |

Alcohols, C11 – C15 secondary ethoxylated

| | | |
|-----------------------------|---------------|---------------|
| Acute Toxicity – oral | LD50 (rat) | > 3,000 mg/kg |
| Acute Toxicity – dermal | LD50 (rabbit) | > 2,000 mg/kg |
| Acute Toxicity – inhalation | LC50 (rat) | No data. |

Solvent naphtha (petroleum), heavy arom.

| | | |
|-----------------------------|---------------|----------------------------------|
| Acute Toxicity – oral | LD50 (rat) | 5 ml/kg |
| Acute Toxicity – dermal | LD50 (rabbit) | > 2 ml/kg |
| Acute Toxicity – inhalation | LC50 (rat) | > 590 mg/m ³ /4 hours |

Other Information:

Metabolic studies on some Azo-dyes, following prolonged skin or oral cavity contact, have detected reduction of azo bonds to aromatic amines. This product, therefore, could potentially metabolize to o-toluidine and o-aminoazotoluene, which have been identified as animal carcinogens, upon prolonged skin or oral cavity contact.

SECTION 12

ECOLOGICAL INFORMATION

Based on data for component materials

12.1 Toxicity:

Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

| | | | | |
|-----------------------|----------------------|-----|-----|--------------------|
| Fish | Onchorhynchus mykiss | LC0 | 96h | 1000 mg/l |
| Aquatic Invertebrates | | | | No data available. |
| Aquatic Plants | | | | No data available |
| Microorganisms | | | | No data available |

Alcohols, C12-C15, branched and linear, ethoxylated, propoxylated

| | | | | |
|-----------------------|------------------|------|-----|----------------------|
| Fish | Leuciscus idus | LC50 | 96h | 1 – 10 mg/l |
| Aquatic Invertebrates | | | | No data available. |
| Aquatic Plants | Algae | EC50 | 72h | Not determined |
| Microorganisms | Activated Sludge | EC10 | | > 1000 mg/l (DEV-L2) |

Alcohols, C11 – C15 secondary ethoxylated

| | | | | |
|-----------------------|---------------------|------|-----|----------------|
| Fish | Pimephales promelas | LC50 | 96h | 3.5 – 4.9 mg/l |
| Aquatic Invertebrates | Daphnia Magna | EC50 | 48h | 3.1 mg/l. |
| Aquatic Plants | Algae | EC50 | 72h | No data. |
| Microorganisms | Activated Sludge | | | No data. |

Solvent naphtha (petroleum), heavy arom.

| | | | | |
|-----------------------|--------------------------|------|-----|-------------|
| Fish | Onchorhynchus mykiss | LL50 | 96h | 2 – 5 mg/l |
| Aquatic Invertebrates | Daphnia magna | EL50 | 48h | 3 – 10 mg/l |
| Aquatic Plants | Raphidocelis subcapitata | EL50 | 72h | 1 – 3 mg/l |
| Microorganisms | Tetrahymena pyriformis | LL50 | 72h | 677.9 mg/l |

12.2 Persistence and degradability:

Moderately biodegradable.

SAFETY DATA SHEET

| | | |
|------|--|---|
| 12.3 | Bioaccumulative potential: | Hydrocarbons C12 - C15 n-alkanes, isoalkanes, cyclics, < 2% aromatics: no data available. The remaining substances in this mixture are not expected to be bioaccumulative. |
| | Partition coefficient: n-octanol/water (log Kow): | Alcohols C11 - C15 secondary ethoxylated log Pow = 3.3 - 4.4 |
| | Bioconcentration factor (BCF): | Alcohols C11 - C15 secondary ethoxylated BCF = 15 – 64 |
| 12.4 | Mobility in soil: | Adsorption to the solid phase is possible. |
| 12.5 | Results of PBT and vPvB assessment: | This mixture does not contain any substances that are assessed to be a PBT or vPvB. |
| 12.6 | Other adverse effects: | No data available. |

SECTION 13 DISPOSAL CONSIDERATIONS

| | | |
|------|---|--|
| 13.1 | Waste treatment methods: | Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation. |
| | Product/packing disposal: | Empty containers may contain residual product and flammable vapours. Do not pierce or burn container even after use. Do NOT remove labels. Keep away from sources of ignition. |
| | Waste codes/waste designations according to LoW: | 16 05 04* gases in pressure containers containing dangerous substances. |

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

| | |
|--|---|
| Waste treatment – relevant information: | Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation |
| Sewage disposal – relevant information: | Do not empty down the drain. |
| Other disposal recommendations: | Use a licensed waste contractor. |

SECTION 14 TRANSPORT INFORMATION

| | | |
|------|------------------------------------|--|
| 14.1 | UN number: | ADR/RID: 1950 IMDG: 1950 IATA: 1950 |
| 14.2 | UN proper shipping name: | ADR/RID: AEROSOLS, flammable IMDG: AEROSOLS, flammable. IATA: AEROSOLS, flammable. |
| 14.3 | Transport hazard class(es): | ADR/RID: 2.1 IMDG: 2.1 IATA: 2.1 |

SAFETY DATA SHEET

| | | | |
|------|--|----------|----------------------|
| 14.4 | Packing group: | ADR/RID: | N/A |
| | | IMDG: | N/A |
| | | IATA: | N/A |
| 14.5 | Environmental hazards: | ADR/RID: | No |
| | | IMDG: | Marine Pollutant: No |
| | | IATA: | No |
| 14.6 | Special precautions for user: | | |
| | ADR/RID – Tunnel code: | (D) | |
| | IMDG – Ems: | F-D, S-U | |
| | IATA/ICAO – PAX: | 203 | |
| | IATA/ICAO – CAO: | 203 | |
| 14.7 | Transport in bulk according to Annex II of Marpol 73/78 and the IBC code: | | |
| | Not applicable. | | |

SECTION 15 REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**
EU Regulations:
 This data sheet complies with the requirements of Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures.
 Safety data sheet as required by EC-Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.
 Regulation (EC) No 648/2004 on detergents.
Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.
 This data sheet is complied according Dir 2013/10/EU, 2008/47/EEC amendment of the aerosol directive 75/324/EEC.
Extra label elements: Pressured container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
 Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.
National regulations (Germany):
Wassergefährdungsklasse (water hazard class): WGK2 – Hazard to waters.
TechnischeAnleitungLuft (TA-Luft): Class 5.2.5 Organic substances, except dusts.
- 15.2 Chemical safety assessment:**
 No chemical safety assessment has been carried out for this mixture by the supplier.

SECTION 16 OTHER INFORMATION

- (i) **Indication of changes:**
 Version 16.1 updated in Section 8 due to updated safety information.
- Vertical lines on the left hand side indicate an amendment from the previous version.
- (ii) **Abbreviations and acronyms:**
- | | |
|-----------|---|
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road (Accord européen relatif au transport international des marchandises Dangereuses par Route) |
| CAS No. | Chemical Abstracts Service number |
| CEN | European Committee for Standardisation |
| CLP | Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008 |
| ECHA | European Chemicals Agency |
| EC50 | Half Maximal Effective Concentration |
| EC number | EINECS and ELINCS number |
| EINECS | European Inventory of Existing Commercial Substances |

SAFETY DATA SHEET

| | |
|---------|---|
| ELINCS | European List of notified Chemical Substances |
| GHS | Globally Harmonized System |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Lethal Concentration to 50% of a test population |
| LD50 | Lethal Dose to 50% of a test population |
| MPI | Magnetic Particle Inspection |
| NDT | Non-Destructive Testing |
| OEL | Occupational Exposure Limit |
| PBT | Persistent, Bioaccumulative and Toxic Substance |
| PMCC | Pensky-Martens closed cup method |
| PPE | Personal Protection Equipment |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation EC (No) 1907/2006 |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail (Reglement International concernant le transport des marchandises Dangereuses par chemin de fer) |
| SDS | Safety Data Sheet |
| STOT RE | Specific Target Organ Toxicity, Repeat Exposure |
| STOT SE | Specific Target Organ Toxicity, Single Exposure |
| TA-Luft | Technical Instructions on Air Quality Control (Technische Anleitung zur Reinhaltung der Luft) |
| vPvB | Very Persistent and Very Bioaccumulative |
| WEL | Workplace Exposure Limit |
| WGK | German Water Hazard Class (Wassergefährdungsklasse) |

(iii) **Key literature and sources of data:**

- Supplier's safety data sheets for components listed in Section 3.
- European Chemicals Agency, <http://echa.europa.eu/>
- GESTIS International Limit Values Database, http://limitvalue.ifa.dguv.de/Webform_gw.aspx
- Occupational Exposure Limits EH40/2005.
- Commission regulation (EU) 2015/830.
- Control of Substances Hazardous to Health Regulations 2002.
- Hazardous waste regulations 2005.
- Health & Safety at Work Act 1974.
- Regulation (EC) 1907/2006 (REACH).

(iv) **Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):**

| Classification according to Regulation (EC) No 1272/2008 | Classification procedure |
|--|--------------------------|
| Aerosol 1: H222, H229 | Test |
| Eye Dam. 1 H318 | Calculation |
| Skin Irr. 2 H315 | Calculation |
| EUH066 | Calculation |

(v) **Hazard statements (number and full text):**

H220: Extremely flammable gas
H222: Extremely flammable aerosol
H229: Pressurised container. May burst if heated.
H280: Contains gas under pressure; may explode if heated.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

Hazard class and category code (full text):

Aerosol 1: Aerosol
Aquatic Chronic 2: Hazardous to the aquatic environment
Aquatic Chronic 3: Hazardous to the aquatic environment

SAFETY DATA SHEET

Asp. Tox. 1: Aspiration Hazard
Eye Dam. 1: Serious eye damage/eye irritation
Eye Irrit. 2: Serious eye damage/eye irritation
Flam. Gas: Flammable Gas
Press. Gas 1: Gases under pressure
Skin Irrit. 2: Skin corrosion/irritation

Relevant precautionary statements (number and full text):

P210: Keep away from heat, sparks, open flames and hot surfaces. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P310: Immediately call a POISON CENTER or doctor/physician.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501: Dispose of contents/container to hazardous waste or special collection point.
P243: Take precautionary measures against static discharge.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.

(vi)

Training advice:

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment. Provide adequate information, instruction and training to operators.

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-to-date and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

| | | |
|--------------------------|--------------------------|--|
| Revision summary: | Revision Comments | This SDS is valid from the Revision Date. If you require a SDS for the product manufactured before the revision date please contact us at datasheets@magnaflux.co.uk . |
| | Revision Date | |
| | Version | 30.10.2015 15.2 |