

# XR150 X-RAY GENERATOR

## Making the unseen seen



Compatible with  
**DeWalt®**  
or  
**Milwaukee®**

**NEW for 2026:  
Smaller  
Lighter  
Faster  
Longer Life**



**Golden Engineering**  
Portable X-ray Technology

**Battery Powered** by DeWalt® 20V or Milwaukee® 18V battery pack

**Versatile** Removable Picatinny Rail to fit in tight spaces

Removable handle options

Threaded insert/Arca Swiss for tripod mounting

**Field-Serviceable** Modular Design with Field-Replaceable Head

**Familiar** Consistent interface with other Golden Models



		XR150 2026
Dimensions	(without battery)	L: 8.7" (22.1 cm)
	(with picatinny rails)	W: 3.42" (8.7 cm)
	(without key)	H: 4.3" (10.9 cm)
Weight	(without battery)	4.43 lbs. (2.01 kg)
X-Ray Energy		150+ kVp
Average Output Dose*		1 mR per pulse
Pulse Rate		37-50 pulses per second
Average Dose* per Second		37-50 mR per second
Operating Temperature		-4 to 158 F (-20 to 70 C)
IP Rating		IP 54

\* Dose measured at 12" (30 cm) from source.

\* Optional equipment shown. Tripod not included.

\* Specifications subject to change pending final design.

 **Golden Engineering**  
Portable X-ray Technology

Contact [sales@goldenengineering.com](mailto:sales@goldenengineering.com)  
for more information or to get a quote