

EchoMix® Single

Powder
Ultrasonic Couplant

EchoMix Single is easily mixed in ambient water in five minutes, providing a gel with a strong, continuous coupling film that adheres well to vertical and overhead surfaces.

PRODUCT DESCRIPTION

Easiest mixing powder couplant; one-packet - no chance of mixing error.

Most economical ultrasonic couplant available.

Blue tracer ensures complete mixing.

Salt stable – will not thin with corrosion salts or in marine or highway environments.

Minimal residue.

Fast, easy removal with water.

Low toxicity, low environmental impact.

Compact for shipping and storing.

Easy mixing, fast time to gel in ambient water (5 minutes to final product).



PRODUCT SPECIFICATIONS

Operating Range: 32° to 120°F (0° to 50°C)

- **Viscosity:** 23,000 CPS,
Brookfield #4 Spindle, 6 rpm
- **pH:** 9
- **Corrosion Inhibition:** Contains mild short term Ferrous Corrosion Inhibitors
- **Compliance:**
ASME Boiler & Pressure Vessel Code (T-533)
NAVSHIPS 250-1500
FAA-AC #25-29 (Glycerin-free)
Less than 0.02% (200 ppm) Halogens & Sulfur

PACKAGING

1 and 5 gallon easy to open and easy to use powder packets.

Cartons of 5, 10, 25, 50 and 100 packets

1-gallon pail with spill proof lid and mixing spoon available.

SDS available at www.echoultrasonics.com



Echo Ultrasonics®, LLC
774 Marine Drive | Bellingham, WA 98225
echoultrasonics.com | sales@echoultrasonics.com
360.671.9121